



COLORS &
EFFECTS

BASF
We create chemistry

Xfast[®] product range for in-plant tinting

Solid pigment preparations for more flexibility in your production

Xfast[®] - the stir-in class

- Smart and Easy to use
- Fully Dispersed Solid Pigment Preparation
- Can make a steep change in your production and in the quality of your final product

Key features include:

- Very high pigment content (up to 85%)
- No sedimentation
- No product residues
- Almost unlimited shelf-life
- Free flowing, low dusting

- Label free according to GHS 2015 and compliant with most eco-labels
- Versatile range with organic and inorganic options to cover the entire color space
- Easier to obtain more opaque coatings

Xfast[®] for in-plant tinting (IPT)

The Xfast[®] product range for exterior and interior applications

Xfast[®] stir-in pigment preparations are innovative, environmentally friendly granules that are applied for the coloration of water based systems. This product range increases your production flexibility and ease of handling while reducing production and storage cost. Xfast[®] ensures your competitive edge, requires no label under the GHS labeling regulations and fulfills all common European labels.

Organic Grades

Xfast [®]	Color Index	Pigment Content [%]	Recommendation
Yellow	0962 P.Y.138	85	Exterior
Yellow	1256 P.Y.74	75	Interior
Yellow	1260 P.Y.154	70	Exterior
Yellow	2350 P.Y.110	75	Exterior
Orange	2931 P.O.67	70	Interior
Orange	3100 P.O.73	75	Exterior
Red	3750 P.R.168	20	Exterior
Red	3855 P.R.112	75	Interior
Red	3860 P.R.254	80	Interior / Exterior
Magenta	4790 P.R.122	80	Interior / Exterior
Violet	5895 P.V.23	80	Interior / Exterior
Blue	7080 P.B.15:3	80	Interior / Exterior
Green	8730 P.G.7	80	Interior / Exterior
Black	0062 P.Bk.7	10	Interior / Exterior
Black	0063 P.Bk.7	70	Interior / Exterior
Black	0066 P.Bk.7	80	Interior / Exterior

Inorganic Grades

Xfast [®]	Color Index	Pigment Content [%]	Recommendation
Yellow	1130 P.Y.184	80	Exterior
Yellow	1916 P.Y.42	60	Wood
Yellow	1990 P.Y.42	80	Interior / Exterior
Red	2817 P.R.101	60	Wood
Brown	2900 P.R.101	80	Interior / Exterior
Brown	2915 P.R.101	80	Interior / Exterior
Red	3390 P.R.101	80	Interior / Exterior
Blue	6310 P.B.28	80	Exterior
Green	9990 P.G.17	80	Exterior
Black	0050 P.Bk.11	80	Exterior
Black	0095 P.Br.29	80	Exterior
White	0025 P.W.6	85	Interior / Exterior

Contacts

Asia Pacific

BASF Colors & Effects Shanghai Ltd.
No 300, Jiang Xin Sha Road
200137 Shanghai
China

EMEA

BASF Colors & Effects GmbH
An der Rheinschanze 1
67059 Ludwigshafen
Germany

Americas

BASF Colors & Effects USA LLC
24710 West Eleven Mile Road
Southfield, MI 48034
USA

Visit our website: www.colors-effects.basf.com

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed. When handling these products, advice and information given in the safety data sheet must be complied with. Further, protective and workplace hygiene measures adequate for handling chemicals must be observed. (07/2017)

® = Registered trademark of the BASF Group